

UL-Listed Couplings Selection Table

H.P.	3500	2900	1750	1450	H.P.		
7 1/2	ROTEX 42	ROTEX 42	ROTEX 42	ROTEX 42	7 1/2		
10					10		
15					15		
20					20		
25			25				
30			30				
40			ROTEX 55	ROTEX 55	ROTEX 55	40	
50						50	
60						60	
75			ROTEX 65	ROTEX 65	ROTEX 65	75	
100	100						
125	ROTEX 65	ROTEX 65	ROTEX 75	ROTEX 75	125		
150					150		
200	C1060T	C1060T	ROTEX 90	ROTEX 90	200		
250					250		
300					300		
350	N/A	N/A	C1080T	C1080T	350		
400					400		
450			N/A	N/A	N/A	N/A	450
500							500
600	N/A	N/A	N/A	N/A	600		
700					700		
800	800						

SIZE	ROTEX 42	ROTEX 55	ROTEX 65	ROTEX 75	ROTEX 90	C1060T	C1080T
Maximum Bore Diameter Inches (mm)	2.125 (52)	2.813 (70)	3.000 (75)	3.625 (92)	4.250 (105)	2.375 (60)	3.375 (85)

NOTES:

- 1) ROTEX is a registered trademark of KTR Corporation.
- 2) C1060T AND C1080T sizes are registered trademarks of Clarke Corporation.
- 3) Coupling selections are for UL-Listed couplings only.
- 4) Couplings cannot be used with diesel engines.
- 5) N/A indicates no UL-listed coupling is available for this horsepower-speed combination.